

PMF-Y3

Proximity Key Fob



- 125 kHz Frequency
- Standard Reinforced Brass Eyelet
- Up to 3.5" (88 mm) Read Range
- 25 Key Fobs Included

Perfect View proximity key fobs set the electronic security benchmark for 125 kHz proximity readers, cards, and tags. Based upon proven contact less digital radio frequency identification (RFID) technology, Perfect View proximity key fobs interface with a wide range of electronic access control systems by complying with the Wiegand communication protocol.

Additionally, proximity key fobs are passive devices and eliminate the need for maintenance by requiring no batteries, and can be ordered to support several proximity reader technologies.

Available Models:
PMF-Y3

Specifications

System Parameters		PMF-Y3
Technology	Proximity	
Frequency	125 kHz	
Operation	Passive (no battery)	
Type	Key fob	
Formats	Wiegand (26-bit and custom formats) and ABA Track II magnetic stripe (clock and data)	
Material	ABS	
Color	Blue	
Slot Punch	Standard reinforced brass eyelet	
Read Range	Up to 3.5" (88 mm)	
Single Key Fob Dimensions	1.2" W × 1.5" H × 0.15" D (30 mm × 38 mm × 3.8 mm)	
Shipping Dimensions (25 Key Fobs)	3.5" W × 2.3" H × 1.8" D (88 mm × 57 mm × 46.8 mm)	
Weight	Single key fob: 0.12 oz (3.6 g)	
	Box of 25 key fobs: 0.2 lbs (90.7 g)	
Operating Temperature	-35° to 122° F (-37° to 50° C)	
Humidity	0% to 95% (non-condensing)	