

PACC-R802 Series

Card Reader



AVAILABLE MODELS

PACC-R802M PACC-R802MK Mifare Card Reader

MAIN FEATURES

- Meets the standard of ISO 14443-A and the card reading frequency is 13.56MHz. The number and content of MIFARE card can be read (PACC-R802M and PACC-R802MK)
- Watchdog design for repairing itself in case that exception occurs, to ensure the long service life
- of the reader
Wiegand(w26, w34) protocol
- Built-in buzzer for identifying the reading status
- IP65 Standard

SPECIFICATION

Model	PACC-R802M	PACC-R802MK		
Power Supply	12V DC			
Power Consumption	≤2W			
Processor	8-bit			
Reading Frequency	13.56MHz			
Reading Range	≤50mm (≤1.97")			
Radio Frequency Standard	ISO 14443-A			
Audio Alert	Beeper			
Keypad	No Keypad (PACC-R802M) Keypad with 12 Keys (0~9, *, #) (PACC-R802MK)			
LED Indicator	Power Indicator, Status Indicator			
Working Temperature	-20°C to +65°C (-4°F to 149°F)			
Working Humidity	10% to 90% (Non Condensing)			
Dimensions	115.9mm×43.3mm×17mm (4.56"×1.70"×0.67")			
Protection Level	IP65			
Installing Method	Wall Mounting with Screws; Do Not Support Gang Box			