

PACC-R200MF - C

IP-based Fingerprint Access Control Terminal



PACC-R200MF-C

PACC-RT200 is a series optical IP-based fingerprint access control terminal with multiple advanced technologies including fingerprint recognition, face detection, Wi-Fi, smart card recognition, LCD displayscreen, and picture capturing technology. It is designed with a 2.8-inch LCD displayscreen, and HDcamera (2 MP). It is equipped with optical fingerprint recognition module

AVAILABLE MODELS

PACC-R200MF-C (with Camera)

MAIN FEATURES

- Doorbell ringtone settings function.
- Touch mode and blue light display technique for keypad.
- Stand-alone settings for the terminal.
- 2.8-inch LCD display screen.
- Transmission modes of wired network (TCP/TP) and Wi-Fi.

- Face detection and picture capturing function implemented by built-in camera (2 MP)
- Supports RS485 communication for connecting external card reader.
- Supports working as a card reader, and supports Wiegand interface and RS485 interface for accessing the controller.
- Max. 100,000 card No., Max. 300,000 access control events records , and Max. 9500 fingerprints storage.
- Adopts the optical fingerprint recognizer module, supporting 1:N mode (fingerprint, card + fingerprint) and 1:1 mode (card + fingerprint).
- Supports multiple authentication modes (card, fingerprint, card + fingerprint, card + password, fingerprint + password, card + fingerprint + password, and so on.)
- Supports Mifare card reading, including card No. reading, and sector reading & writing (PACC-RT200MF-C)
- Tampering detection, unlocking overtime alarm, invalid card swiping over times alarm, duress card alarm, and so on.
- Accurate data and time display provided by built-in electronic clock and watchdog program to ensure the basic function of the terminal.
- Data can be permanently saved after power-off.

SPECIFICATIONS

Model Parameters	PACC-RT200M-C
Processor	≥1GHz, 32 Bit High-performance Processor
Storage	256M Storage
Micro SD Card (Additional)	Max.32G, Built-in Micro SD Card
Operation System	Linux
Camera	2 MP (Optional)
Valid Card/ Swiping Record	100/300 thousand
Fingerprint Capacity	Max. 4750 People (Two Local Collected Fingerprint Templates for Each, Person, 9500 Fingerprints in Total)
Fingerprint Recognition Duration	1:1≤1s, 1:1000≤1s
FAR (False Accept Rate)	≤0.001%
FRR (False Rejection Rate)	≤0.01%
Fingerprint Recognizer	Optical Fingerprint Recognizer Module
Card Reading Mode	Supports Mifare card reading, including card No. reading, and sector reading & writing (PACC-RT200MF-C)
Card Reading Frequency	Mifare Card (PACC-R200MF-C): 13.56MHz
External Card Reader	RS485 IC Reader
Communication Mode	TCP/IP, WIFI, RS-485, and Wigand 26/34 (under the card reader mode only)
Transmission Rate	TCP/IP, WIFI: 10/100Mbps Self-adaptive, RS-485: 19200 bps-N-8-1
Input Interface	Door Switch Key×1, Magnetic Door×1, Relay ×1, Alarm×2
Output Interface	Doorbell×1, Relay×1
LCD Screen	320×240 LCD-TFT Display Screen
Key Board	16 Keys (0 to 9, F1, DEL, Switch Key, *, #, Doorbell)
LED Indicator	Power/ Communication
Audio	Loudspeaker
Power Supply	12VDC
Working Current	500mA (without Locks)
Working Temperature	-20°C to 65°C
Working Humidity	10% to 90% (No Condensing)
Certificate	CE, FCC
Dimension	122×142×27mm (4.8×5.6×1.1")
Weight	400g (0.88lb)