Coaxial Cabling : HD-TVI/AHD/HDCVI Distributor & Video Amplifier

ITEM NO.: CD102HD HD-TVI/AHD/HDCVI 1 input 2 output Video Distributor



CD102HD is 1 input 2 output HD-CVI/TVI/AHD Video distributor. They are suitable for far distance, different floor in a building or different electrical field.


CD102HD HD-TVI/AHD/HD-CVI 1 input 2 output Video Distributor Features:

- 1 Video input to 2 video output.
- Support HD-TVI, AHD, HDCVI, 960H, NTSC, PAL video signal.
- Support high resolution up to 4K/1080P without any video loss.
- Built in green LED for power on/off detection.
- Built in TVS protection.

Installation View:



Panel View:



LED Indication:

GREEN

ON Power ON OFF Power OFF

Cable:

Link cable recommend to use high quality 75 Ω Coaxial Cable and BNC connector, low quality coaxial cable may case signal loss and effect transmission distance and reliability.

Specifications:

Specifications:	
ITEM NO.	CD102HD
Video Input Channel	BNC x 1
Video Output Channel	BNC x 2
Video Input Level	0.8~1.2Vp-p, 75 Ohms
Video Output Level	1Vp-p (Standard), 75 Ohms
Video Bandwidth	350 MHz -3dB
Power Supply	DC12V 500mA
Power Consumption	160mA
Temperature	Operation: 0 to 55° , Storage: -20 to 85° , Humidity: up to 95°
Dimensions mm	57.8 x 49.2 x 41.7
Weight g	70

1

