

PTA-TPP016HD



Features

16 PORT HD PASSIVE VIDEO TRANSCEIVER IN 1U RACK MOUNTING PANEL
FOR HD-CVI/HD-TVI/AHD

- Built in 16 port passive HD video transceiver in 1U 19" rack mounting panel.
- Choice of 4 x RJ45 or 4 sets x 8 pin removable screw terminal for 16 channel inputs/outputs.
- To send HD-CVI, AHD signal up to 300M over UTP cable.
- To send HD-TVI signal up to 200M over UTP cable.
- Passive, NO power required.
- Eliminate Coaxial Cable.
- To work with Active Transmitter HTA-TTA111HDT, HTA-TTA111TVIT for extra long distance transmission.
- Built in ESD, EFT (Impulse noise) and transient protection.

Specifications

Model Name	PTA-TPP016HD
Video Input/Output	BNC x 16 (1Vp-p, 75 Ohm)
RJ45 Output	8 Pin removable terminal x 4 (100 Ohm) / RJ45 x 4
Cable	CAT5e / CAT6 UTP
Bandwidth	50Hz ~ 60MHz (-3dB)
Transmission Distance	HD-CVI / AHD: 300 meters HD-TVI: 200 meters
ESD Protection	30KV (Air), 15KV (Contact); IEC 61000-4-2 compliant
EFT Protection	40A (5/50ns); IEC 61000-4-4 compliant
Lightning Protection	2A (8/20µs); IEC 61000-4-5 compliant
Environmental Specifications	Operation: 0° to 55°C, Storage: -20° to 85°C, Humidity: up to 95%
Dimensions (mm)	483 x 103.3 x 44 (1U)

Specifications

Weight (g)	1380
------------	------