

HEAR504-08



Features

8-ch H.264/MPEG4/MPEG2/MJPEG Video Encoder

- H.264/MPEG4/MPEG2/MJPEG encoding standards supported
- Support encoding video at up to 4CIF resolution
- One independent PoE network interfaces
- Connectable with network HDD in NAS, IPSAN mode
- Support multiple network protocols, including IPv4/v6, HTTP, HTTPS, QoS layer3 DiffServ, FTP, SMTP, Bonjour, UPnP, SNMPv1/v2c/v3, OnVIF, PSIA, SOCKSv4/v5, etc.;
- Multiple PTZ protocols

Specifications	
Model Number	HEAR504-08
Video Compression	H.264 / MPEG4 / MPEG2 / MJPEG
Video input	8-ch, BNC (1.0Vp-p, 75)
Audio Compression	G.711u
Audio input	4-ch RCA (2.0 Vp-p, 1 K)
Two-way audio input	1-ch
Audio output	1-ch RCA (Linear, 1 K)
Recording resolution	1080P/720P/WD1/4CIF/VGA/CIF
Frame rate	1/16 fps to real time frame rate
Video bit rate	32 Kbps ~ 10 Mbps
Audio bit rate	64 Kbps

Specifications	
Dual-stream	Support
Stream type	Video, Video & Audio
Type	NAS, iSCSI, IPSAN
Capacity	2 internal SATA up to 8TB ea.
Network interface	1 RJ-45 10M/100 Mbps adaptive Ethernet interface (PoE)
Protocols	IPv4/v6, HTTP, HTTPS, QoS layer3 DiffServ, FTP, SMTP, Bonjour, UPnP, SNMPv1/v2c/v3(MIB-11), DNS, DynDNS, hkDDNS, NTP, RTSP, RTP/RTCP, TCP, UDP, IGMP, ICMP, DHCP, ARP, SOCKSv4/v5, PSIA, OnVIF, Hik CGI, netFilter
Serial interface	1 half-duplex RS-485 interface
Alarm in	8
Alarm out	4
Power supply	12 VDC
Consumption	< 30W
Working temperature	-10 °C ~ +55 °C
Working humidity	10% ~ 90%
Dimensions (W x D X H)	14.96" × 11.42" × 1.89"
Weight	4.41 Lbs

X