

## HKH8300-T Video Intercom Indoor Station With 7-inch Touch Screen



### Key Features

#### Basic Functions

- Hands-free audiovisual communication with the door station and the master station in the intercom system
- 8-ch zone alarm supported
- Panic call supported
- Supports monitoring door stations and external cameras
- Remote unlocking via the client software
- High-performance embedded SOC processor
- TF card supported

#### Video/Audio Functions

- HD video surveillance
- 7-inch colorful FTF LCD with resolution 1024x600
- Capacitive touch screen and touch keys
- Noise suppression and echo cancellation

#### Alarm Functions

- 8-ch alarm input sensor supported
- Auto-uploads alarm message to the master station or the client software once the alarm is triggered


#### Remote Controls

- Remote reboot, remote upgrade, time synchronization via NTP, and batch configuration function
- Supports web remote access and OSD display
- Supports motion detection

#### Additional Features

- Community notice supported
- Convenient installation and easy operation

#### Application




## Specifications

<b>System Parameters</b>	
Processor	High-Performance Embedded SOC Processor
Operation System	Embedded Linux Operation System
<b>Display Parameters</b>	
Display Screen	7-inch colorful TFT LCD
Display resolution	1024x600
Operation method	Capacitive Touch Screen, Touch Key
Operation Interface	Flattened UI Operation Interface
<b>Audio Parameters</b>	
Audio input	Built-in Omnidirectional Microphone
Audio Output	Built-in Loudspeaker
Audio compression standard	G.711U
Audio compression rate	64 Kbps
Audio quality	Noise Suppression and Echo Cancellation
<b>Network Parameters</b>	
Alarm input	8-ch Alarm Input Sensor
Protocols	RTP, TCP/IP
Ethernet	10/100 Mbps Self-Adaptive Ethernet
<b>Device Interface</b>	
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface
RS-485	1 RS-485 Half-Duplex Port
I/O input	2
TF card (micro SD card)	TF Card, Support Max 32GB
<b>General</b>	
Operating Conditions	-10 °C to 55 °C (-14 °F to +131 °F), Humidity 10% to 90%
Power Supply	24 VDC, Power Over Network Cable 12 VDC
Power Consumption	10 W Max
Memory	256 M
Dimensions	217 mm x 142 mm x 26 mm ( 8.5" x 5.6" x 1.0")
Certification	FCC, IC, CE, C-TICK, ROHS, REACH, WEEE

## Available Models:

HDB301-VP

## Appearance and Interfaces



Index	Description	Index	Description
1	Power Supply Indicator	9	Microphone
2	Information Indicator	10	TF Card Slot
3	Alarm Indicator	11	Serial Port
4	SOS Touch Key	12	Terminals
5	Unlock Touch Key	13	Power Supply Interface
6	Live View Touch Key	14	Network Interface
7	Management Center Touch Key	15	Loudspeaker
8	LCD Display Screen		