

PNCT325-XDLU/2.8



Specifications

Model Number	PNCT325-XDLU/2.8
Image Sensor	1/2.7" progressive scan CMOS
Min. illumination	Color: 0.03 Lux @ (F2.0, AGC ON), 0 Lux with illumination on
Shutter time	1/5 ~ 1/32,000s
Lens	2.8mm
Angle adjustment	Pan: 0° ~ 360°, tilt 0° ~ 70°, Rotation: 0 ~ 360°
Digital noise reduction	Yes
Wide dynamic range	120dB
Day & night	ICR
Video compression	Main stream: H.265/H.264/H.264+/H.265+, Sub-stream: H.265/H.264/MJPEG, Third stream: H.265/H.264/MJPEG
Triple stream	Yes
Audio In	Yes
Alarm	1/1
Max. image resolution	2560×1920
Frame rate	60 Hz: 30 fps (2560 x 1920, 2560 × 1440, 1920 × 1080, 1280 × 720)

Specifications

Image settings

General settings	Video title and time stamp overlay, video orientation (flip, mirror, rotation), day/night settings
Illuminators	Illuminators, anti-overexposure/smart IR
Image settings	White balance, image adjustment (brightness, contrast, saturation, sharpness, gamma curve), defog, 3DNR
Exposure	BLC, HLC, exposure control (exposure level, exposure time, gain control), AE speed adjustment, WDR Privacy mask Pixel calculator Scheduled profile settings

BLC	Yes
-----	-----

On Board Storage	Micro SD slot, up to 256GB
------------------	----------------------------

Protocols	802.1X, ARP, Bonjour, CIFS/SMB, DDNS, DHCP, DNS, FTP/SFTP, HTTP, HTTPS, ICMP, IGMPv3, IPv4, IPv6, NTCIP, NTP, PPPoE, QoS (CoS/DSCP), RTSP/RTP/RTCP, SMTP, SNMP, SSL, TCP/IP, TLS 1.2/1.3, UDP, UPnP
-----------	---

ONVIF	Profile G, S, T supported, Onvif 21.06
-------	--

Security	Access list, CSRF protection, digest authentication, HTTPS , IEEE 802.1x, Password protection, signed firmware, Trend Micro IoT Security (brute force attack event, cyberattack event, quarantine event), user access log, user account management
----------	--

Communication interface	1 RJ45 10M / 100M Ethernet interface
-------------------------	--------------------------------------

Operating conditions	-30°C ~ 60°C (-22°F ~ 140°F) humidity 95% or less (non-condensing)
----------------------	--

Specifications

Power supply	12 VDC $\pm$ 25%, 0.7 A, max. 5.5 W
Power consumption	PoE: IEEE 802.3af, Class 3, max. 5.5 W
Ratings	IP67
Range	Up to 90ft both IR and White Light
Dimensions	Ø5.3" $\times$ 3.7"
Weight	1.1lbs
Electrical Box	
Wall Mount	
Pendant	
Corner and Pole	C: P-276ZJ, P: P-275ZJ