

HAC303D-VB4

HD720P Turbo HD Outdoor Vari-focal IR Bullet Camera



Key Features

- HD720P Video Output
- Adopt HDTV Technology
- True Day/Night
- 2.8-12mm vari-focal lens
- OSD menu, eD DNR, Smart IR
- Up to 40m IR distance
- Low illuminations
- Up the Coax(via coaxial cable)

Specifications

Camera	
Image Sensor	1.3MP CMOS Image Sensor
Signal System	PAL/NTSC
Effective Pixels	1305(H)*1049(V)
Min. illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Time	1 / 60 s to 1 / 50,000 s
Lens	2.8-12mm @ F1.4 Angle of view: 78° - 28°
Lens Mount	φ14
Day & Night	ICR
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 180°, Rotation: 0 - 360°
Synchronization	Internal Synchronization
Video Frame Rate	720p@60fps
HD Video Output	1 Analog HD output
S/N Ratio	>62dB
Menu	
Automatic Exposure	Globe AE/DWDR
AGC	Low/Middle/High/Off
Slow Shutter	Support
White Balance	Auto/Manual
D/N Mode	Color/BW/Smart IR
3D DNR	Low/Middle/High/Off
Motion Detection	Support, maximum 4 zones
Privacy Mask	On/Off, maximum 8 zones
UTC Function	Support
Language	English/Chinese
Function	Digital Wide Dynamic Range, 3D Digital Noise Reduction, Sharpness, Brightness, Digital Zoom, Mirror
General	
Operating Conditions	30 °C - 60 °C (-22 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC ; -A: 12 VDC, 24 VAC
Power Consumption	12 VDC: Max. 4W ; 24 VAC: Max. 6W
Protection Level	IP66
IR Range	Up to 40m
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)
Dimensions	105 × 86.9 × 267.2mm(φ 4.13" x 3.42" x 10.52")
Weight	1350g (2.97 lb)