

HAC304D-VBM



Features

IVMS HD-TVI 1080P Turbo HD Outdoor Motorized Vari-focal EXIR Bullet Camera

- HD1080P Video Output
- Adopt HDTV Technology
- True Day/Night
- 5-50mm vari-focal lens
- Motorized Vari-focal Len
- 42 pcs IR LEDs
- OSD menu, 3D DNR, Smart IR
- Up to 400ft IR distance
- Up the Coax(via coaxial cable)
- 120 dB True Wide Dynamic Range

Specifications

| | |
|--------------------|---|
| Model Number | HAC304D-VBM |
| Image Sensor | 1 / 3" Progressive Scan CMOS |
| Signal System | PAL / NTSC |
| Effective Pixels | 1920(H)*1080(V) |
| Min. Illumination | 0.01 Lux @ (F1.2,AGC ON),0 Lux with IR 0.014 Lux @ (F1.4,AGC ON),0 Lux with IR |
| Shutter speed | 1/25 s to 1/50,000 s |
| Lens | 5-50mm |
| Lens Mount | 14 |
| Day & Night | ICR |
| Wide dynamic range | True WDR 120 dB |
| Synchronization | Internal synchronization |

| Specifications | |
|--------------------------------|---|
| Video Frame Rate | 1080p@25fps/1080p@30fps |
| HD Video Output | 1 Analog HD output |
| CVBS Output | 1Vp-p Composite Output(75 / BNC) |
| S / N Ratio | More than 52dB |
| Scene | Indoor, Outdoor, Indoor1, LOW-LIGHT |
| Camera ID | On/off (15 characters, position programmable) |
| AGC | Support |
| D/N Mode | Color/BW/EXT |
| White Balance | ATW, AWC-SET, Indoor, Outdoor, Manua |
| Privacy Mask | On/Off, maximum 8 zones |
| Motion Detection | On/Off, maximum 4 zones |
| BLC | Support |
| Anti-flicker | On/off |
| Language | English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic |
| Function | Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM |
| Working Temperature / Humidity | -20 °C – 60 °C (-4 °F – 140 °F) Humidity 90% or less (non-condensing) |
| Power Supply | 12 VDC ; -A: 12 VDC, 24 VAC |
| Power Consumption | 12V DC: Max. 7W ; 24V AC: Max. 10W |
| Weather Proof Ratings | IP66 |
| IR Range | Up to 400 ft |
| Communication | Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron) |
| Dimensions | 300.82×100.76×107.55mm(11.84”×3.97”×4.23”) |
| Weight | 700 g (1.54 lbs) |