

## HAC334D-OD4ZB



### Features

IVMS HD-TVI 1080P Turbo HD Outdoor Motorized Vari-focal Dome Camera

- HD1080P Video Output
- Adopt HDTV Technology
- True WDR
- True Day/Night
- 2.8 – 12mm vari-focal lens
- Motorized Vari-Focal Len
- 24 pcs IR LEDs
- OSD menu, 3D DNR, Smart IR
- Up to 120ft IR distance
- Up the Coax(via coaxial cable)

### Specifications

Model Number	HAC334D-OD4ZB
Image Sensor	2MP CMOS Sensor
Signal System	PAL / NTSC
Effective Pixels	1928(H)*1088(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	1/25 s to 1/50,000 s

Specifications	
Lens	2.8~12mm
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
Wide Dynamic Range	True WDR
S / N Ratio	More than 52dB
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manual
Privacy Mask	On/Off, maximum 2 zones
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Language	English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic
Function	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
Working Temperature / Humidity	-40 °C – 60 °C (-40 °F – 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC ;24 VAC
Power Consumption	12V DC: Max. 4.5W 24V AC: Max. 6.5W
Ratings	IP66, IK10
IR Range	Up to 120 ft
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)
Dimensions	145.3 × 124.2 mm (5.72” × 4.89”)
Weight	3.53 lbs